

- ▶ Safe and easy access recommended to a depth of 5.00 m
- ▶ David and fall protection device, for safely entering and exiting the construction trench
- ▶ Rescue injured workers
- ▶ Easily and safely attach your ladders
- ▶ CE-certified
- ▶ Suitable for all SBH shoring systems
- ▶ Lightweight fall protection, compliant with DIN EN
- ▶ Lengths from 0.5 m to 3.00 m with weights from 8.0-38.0 kg. With additional 2.6-3.5 kg per barrier post
- ▶ Optimum protection for workers on your construction site
- ▶ 2-person assembly

FALL PROTECTION



FALL PROTECTION BARRIERS

Description	Length [m]	Dimensions b x h [mm]	Weight [kg]
Barrier	0.50	30.00 x 1060.00	16.0
Barrier	1.50	30.00 x 1060.00	19.0
Barrier	2.00	30.00 x 1060.00	22.0
Barrier	2.50	30.00 x 1060.00	25.0
Barrier	3.00	30.00 x 1060.00	28.0



FALL PROTECTION

Description	Dimensions b x h x t [mm]	Working length Total [m]	Fall arrest Total [kN]	Lifting load Total [kg]	Weight [kg]
David set	- 261.00 x 855.00 x 2730.00	15.00	6.0	135.0	- 55.5



Gap closure for sealing and securing unsecured corners of construction trenches.

EASY ACCESS

Description	Dimensions b x h x t [mm]	Weight [kg]
Easy access	- 1620.00 x 1250.00 x 1400.00 (inc ladder latch)	165.0 kg

